

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cutting Fluid Silberschnitt V63

Revision: 04.05.2026

Product code: BO5002903

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Cutting Fluid Silberschnitt V63

Further trade names

BO5002903, 30 l

BO5002933, 200 l

BO9973880*, Sample

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

cutting fluid

1.3. Details of the supplier of the safety data sheet

Company name: BOHLE AG

Street: Dieselstr. 10

Place: D-42781 Haan

Telephone: +49 2129 5568-0

Telefax: +49 2129 5568-282

E-mail: info@bohle.de

Contact person: Dr. Martin Schade

Telephone: +49 2129 5568-300

E-mail: MSDS@bohle.de

Internet: www.bohle.com

Responsible Department: Chemie

1.4. Emergency telephone

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Hydrocarbons, C11-C14, n-alkane, isoalkanes, cyclics, <2% aromatics

Signal word: Danger

Pictograms:



Hazard statements

H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Cutting Fluid Silberschnitt V63

Revision: 04.05.2026

Product code: BO5002903

Page 2 of 9

Chemical characterization

Hydrocarbons

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
93924-45-9	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics			>70 %
	920-107-4		01-2119453414-43	
	Asp. Tox. 1; H304			
93924-07-3	Hydrocarbons, C11-C14, n-alkane, isoalkanes, cyclics, <2% aromatics			<25 %
	926-141-6		01-2119456620-43	
	Asp. Tox. 1; H304			
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether			<10 %
	203-961-6	603-096-00-8	01-2119475104-44	
	Eye Irrit. 2; H319			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
93924-07-3	926-141-6	Hydrocarbons, C11-C14, n-alkane, isoalkanes, cyclics, <2% aromatics	<25 %
		dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
112-34-5	203-961-6	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	<10 %
		dermal: LD50 = 4120 mg/kg; oral: LD50 = 5660 mg/kg	

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

First aider: Pay attention to self-protection!
Move out of dangerous area.
Take off contaminated clothing and shoes immediately.

After inhalation

Remove casualty to fresh air and keep warm and at rest.
If symptoms persist, call a physician.

After contact with skin

Wash off with soap and plenty of water.
If symptoms persist, call a physician.

After contact with eyes

Rinse thoroughly with plenty of water, also under the eyelids. Remove contact lenses, if present and easy to do. Continue rinsing.
Consult a physician.

After ingestion

Rinse mouth thoroughly with water.
Do NOT induce vomiting.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways.
Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

Cutting Fluid Silberschnitt V63

Revision: 04.05.2026

Product code: BO5002903

Page 3 of 9

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂)
Extinguishing powder
alcohol resistant foam
Water spray jet

Unsuitable extinguishing media

high volume water jet

5.2. Special hazards arising from the substance or mixture

Heating or fire can release toxic gas.
Carbon dioxide, Carbon monoxide

5.3. Advice for firefighters

Standard procedure for chemical fires.
Self-contained respirator (breathing apparatus)

Additional information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Use personal protective equipment.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.
Do not allow to enter into soil/subsoil.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**Other information**

Provide adequate ventilation.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Dispose of waste according to applicable legislation.

6.4. Reference to other sections

Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation as well as local exhaust at critical locations.
To avoid risks to man and the environment, comply with the instructions for use.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Usual measures for fire prevention.
Take precautionary measures against static discharges.
Vapours can form explosive mixtures with air.

Cutting Fluid Silberschnitt V63

Revision: 04.05.2026

Product code: BO5002903

Page 4 of 9

Advice on general occupational hygiene

Do not breathe vapours or spray mist.
Avoid contact with skin, eyes and clothing. Take off all contaminated clothing immediately.
Wash hands before breaks and immediately after handling the product.
When using do not eat or drink. Do not smoke.
Keep away from food, drink and animal feedingstuffs.

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.
Store in a place accessible by authorized persons only.
Protect from direct sunlight.

Hints on joint storage

Incompatible with oxidizing agents.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C

7.3. Specific end use(s)

cutting fluid

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	
		15	101.2		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether			
Worker DNEL, long-term		dermal	systemic	20 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	67,5 mg/m ³
Worker DNEL, long-term		inhalation	local	67,5 mg/m ³

PNEC values

CAS No	Substance	Value
Environmental compartment		
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	
Freshwater		1 mg/l
Marine water		0,4 mg/l

8.2. Exposure controls
Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment
Eye/face protection

safety glasses with side-shields conforming to EN166

Cutting Fluid Silberschnitt V63

Revision: 04.05.2026

Product code: BO5002903

Page 5 of 9

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Glove material: Butyl caoutchouc (butyl rubber), NBR (Nitrile rubber)

Take note of the information given by the producer concerning permeability and break through times , and of special workplace conditions (mechanical strain, duration of contact).

Skin protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

EN 13034 (type 6 limited splash-tight)

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Combination filtering device

Respirator with filter for organic vapour, Recommended Filter type: A-P2

Environmental exposure controls

Do not flush into surface water or sanitary sewer system.

Do not allow to enter into soil/subsoil.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	like: Hydrocarbons	
Boiling point or initial boiling point and boiling range:	> 190 °C	Test method
Lower explosion limits:	not determined	
Upper explosion limits:	not determined	
Flash point:	>90 °C	ISO 2719
Auto-ignition temperature:	not determined	
pH-Value (at 20 °C):	6	
Viscosity / kinematic: (at 40 °C)	< 2 mm²/s	
Water solubility:	insoluble	
Vapour pressure: (at 20 °C)	>0,1 hPa	
Density (at 20 °C):	0,83 g/cm³	

9.2. Other information

Information with regard to physical hazard classes

Sustained combustibility:	No sustained combustibility
Self-ignition temperature	not auto-flammable

Other safety characteristics

Solvent content:	20,00 %
Viscosity / dynamic: (at 20 °C)	< 3 mPa·s

Further Information

Vapours can form explosive mixtures with air.

SECTION 10: Stability and reactivity

Cutting Fluid Silberschnitt V63

Revision: 04.05.2026

Product code: BO5002903

Page 6 of 9

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Protect from direct sunlight.

10.5. Incompatible materials

oxidizing agents

10.6. Hazardous decomposition products

No decomposition if used as directed.

SECTION 11: Toxicological information
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
93924-07-3	Hydrocarbons, C11-C14, n-alkane, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 >5000 mg/kg	Rat	OECD 401	
	dermal	LD50 >5000 mg/kg	Rabbit	OECD 402	
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether				
	oral	LD50 5660 mg/kg	Rat		
	dermal	LD50 4120 mg/kg	Rabbit		

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Cutting Fluid Silberschnitt V63

Revision: 04.05.2026

Product code: BO5002903

Page 7 of 9

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards
Endocrine disrupting properties

This information is not available.

SECTION 12: Ecological information
12.1. Toxicity

This product has no known eco-toxicological effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether					
	Acute fish toxicity	LC50 mg/l	1300	96 h	Lepomis macrochirus (Bluegill)	
	Acute algae toxicity	ErC50 mg/l	> 100		Scenedesmus sp.	
	Acute crustacea toxicity	EC50 mg/l	2850	48 h	Daphnia pulex (water flea)	
	Fish toxicity	NOEC mg/l	>100	4 d	Desmodesmus subspicatus	

12.3. Bioaccumulative potential

Bioaccumulation is unlikely.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	0,56 (25°C)

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

slightly water endangering

Do not flush into surface water or sanitary sewer system.

Avoid subsoil penetration.

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Disposal recommendations

Can be incinerated, when in compliance with local regulations.

Contaminated packaging

Dispose of completely emptied containers as combustible waste or metal waste depending on the material.

SECTION 14: Transport information
Land transport (ADR/RID)

Cutting Fluid Silberschnitt V63

Revision: 04.05.2026

Product code: BO5002903

Page 8 of 9

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Other applicable information

Not dangerous goods in the meaning of ADR/RID, ADN, IMDG-Code, ICAO/IATA-DGR

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 55, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 5 % (41,5 g/l)

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

Asp. Tox. 1: Aspiration hazard, hazard category 1

Eye Irrit. 2: Eye irritation, hazard category 2

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
EUH066	Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cutting Fluid Silberschnitt V63

Revision: 04.05.2026

Product code: BO5002903

Page 9 of 9

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)