Safety Data Sheet

according to 29 CFR 1910.1200(g)

UV Adhesive VERIFIX B 665-0

1. Identification

Product identifier

UV Adhesive VERIFIX B 665-0

Further trade names

BO 5209327, 20 g
BO 5209300, 100 g
BO 5209321, 250 g
BO 5209324, 1000 g

Recommended use of the chemical and restrictions on use

Use of the substance/mixture

adhesives

Details of the supplier of the safety data sheet

Manufacturer

Company name:	BOHLE AG	
Street:	Dieselstr. 10	
Place:	D-42781 Haan	
Telephone:	+49 2129 5568-0	Telefax: +49 2129 5568-282
E-mail:	info@bohle.de	
Contact person:	Dr. Martin Schade	Telephone: +49 2129 5568-300
E-mail:	MSDS@bohle.de	
Internet:	www.bohle.com	
Responsible Department:	Chemie	

Supplier

Company name:	Bohle America / Portals Hardware
Street:	925 Lydia Ave
Place:	Kansas City, MO 64106 USA
Telephone:	+1 888 838 6006
E-mail:	support@portalshardware.com

Emergency phone number: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

2. Hazard(s) identification

Classification of the chemical

29 CFR Part 1910.1200

Flammable liquids: Category 4
Skin corrosion/irritation: Category 2
Serious eye damage/eye irritation: Category 1
Respiratory or skin sensitization: Skin sensitization, category 1
Specific target organ toxicity single exposure: Category 3 (respiratory tract irritation)

Label elements

29 CFR Part 1910.1200

Signal word: Danger

Pictograms:



Hazard statements

Causes skin irritation

May cause an allergic skin reaction
Causes serious eye damage
May cause respiratory irritation
Harmful to aquatic life with long lasting effects

Precautionary statements

Wear protective gloves/protective clothing/eye protection/face protection.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
If skin irritation or rash occurs: Get medical help.

3. Composition/information on ingredients

Mixtures

Chemical characterization

Methacrylate/Acrylate resin(s).

Relevant ingredients

CAS No	Components	Quantity
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	39 %
868-77-9	2-hydroxyethyl methacrylate	39 %
79-10-7	acrylic acid, prop-2-enoic acid	4.9 %
110-16-7	maleic acid	2.9 %
614-45-9	tert-butyl perbenzoate	2.9 %
2530-85-0	3-methoxysilylpropyl methacrylate	0.9 %

4. First-aid measures

Description of first aid measures

General information

First aider: Pay attention to self-protection!
Get medical advice/attention if you feel unwell.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If symptoms persist, call a physician.

After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. When in doubt or if symptoms are observed, get medical advice.

After contact with eyes

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

After ingestion

Do not induce vomiting. Immediately give large quantities of water to drink. Call a physician immediately.

Most important symptoms and effects, both acute and delayed

Inhalation: Irritation to respiratory tract
Skin contact : May cause an allergic skin reaction.
Eye contact : Causes serious eye damage.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Water spray jet, Extinguishing powder, Foam, Carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

Specific hazards arising from the chemical

Burning produces irritant fumes. Carbon monoxide, Carbon dioxide, Hydrocarbons, Nitrogen oxides (NOx)

Special protective equipment and precautions for fire-fighters

Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
In the event of fire, wear self-contained breathing apparatus.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

General advice

Wear personal protection equipment (refer to section 8).
Provide adequate ventilation.

Environmental precautions

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.
Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Other information

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal. Ensure adequate ventilation.

Reference to other sections

Personal protection equipment (PPE): see section 8
Disposal: see section 13

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Avoid contact with skin and eyes.
Do not eat, drink or smoke when using this product.
Ensure adequate ventilation.

Advice on protection against fire and explosion

No special technical protective measures required.

Advice on general occupational hygiene

Wash hands before breaks and after work. When using do not eat, drink or smoke.
Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.

Further information on handling

Avoid: UV-radiation/sunlight

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place.
Keep container tightly closed. Keep locked up.
Recommended storage temperature 5 - 25°C. Keep away from direct sunlight.

8. Exposure controls/personal protection

Control parameters

Exposure limits

CAS No	Substance	ppm	mg/m³		Category	Origin
79-10-7	Acrylic acid	2	6		TWA (8 h)	REL

Exposure controls

Appropriate engineering controls

Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapour. To follow: Occupational exposure limit values

Individual protection measures, such as personal protective equipment

Eye/face protection

safety glasses with side-shields conforming to EN166

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.
Recommended material: NBR (Nitrile rubber), VITON
Unsuitable material: Natural fibres (e.g. cotton)

Skin protection

Wear suitable protective clothing.

Respiratory protection

Usually no personal respirative protection necessary. When using do not eat, drink or smoke.
In case of inadequate ventilation wear respiratory protection. Full-/half-/quarter-face masks (EN 136/140)
Respirator with filter for organic vapour. Recommended Filter type: A (P2)

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Liquid	
Color:	colorless	
Odor:	characteristic	
		Test method
Flash point:	101 °C	
Auto-ignition temperature:	238 °C	
pH-Value (at 21 °C):	2	5% emulsion
Water solubility:	practically insoluble	

Other information

Information with regard to physical hazard classes

Explosive properties

None.

Other safety characteristics

Solvent content:	0%
Viscosity / dynamic: (at 25 °C)	55 mPa·s

10. Stability and reactivity

Reactivity

Light / UV-radiation/sunlight
Oxidizing agent, strong

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

No known hazardous reactions.

Conditions to avoid

Keep cool. Protect from sunlight. Heat, flames and sparks.
In case of light influence: Polymerisation

Incompatible materials

Reducing agent, strong. Oxidizing agent, strong
strong acids and strong bases

Hazardous decomposition products

No decomposition if stored and applied as directed.
Thermal decomposition can lead to the escape of irritating gases and vapors. Carbon monoxide (CO), Carbon dioxide (CO2), Hydrocarbons

11. Toxicological information

Information on toxicological effects

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 5000 mg/kg

Acute toxicity

CAS No	Components					
	Exposure route	Dose		Species	Source	Method
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate					
	oral	LD50 mg/kg	>5000	Rat		
	dermal	LD50 mg/kg	>5000	Rabbit		
868-77-9	2-hydroxyethyl methacrylate					
	oral	LD50 mg/kg	5050	Rat		
	dermal	LD50 mg/kg	>5000	Rabbit		
79-10-7	acrylic acid, prop-2-enoic acid					
	oral	LD50 mg/kg	500	Rat		
	dermal	LD50 mg/kg	1100	Rat		
	inhalation (4 h) vapour	LC50	11 mg/l	Rat		
	inhalation dust/mist	ATE	1,5 mg/l			
110-16-7	maleic acid					
	oral	LD50 mg/kg	1090	Rat	OECD 401	
	dermal	LD50 mg/kg	1560	Rabbit		
614-45-9	tert-butyl perbenzoate					
	oral	LD50 mg/kg	4838	Rat		
	dermal	LD50 mg/kg	3817	Rabbit		
	inhalation vapour	ATE	11 mg/l			
	inhalation dust/mist	ATE	1,5 mg/l			
2530-85-0	3-methoxysilylpropyl methacrylate					
	oral	LD50 mg/kg	>5000	Rat		

Carcinogenicity (OSHA): No ingredient of this mixture is listed.

Carcinogenicity (IARC): Acrylic acid (CAS 79-10-7) is listed in group 3.

Carcinogenicity (NTP): No ingredient of this mixture is listed.

Information on other hazards

Endocrine disrupting properties

This information is not available.

12. Ecological information

Mobility in soil

This information is not available.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

This information is not available.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Consult the appropriate local waste disposal expert about waste disposal.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

14. Transport information

Marine transport (IMDG)

UN number or ID number:	No dangerous good in sense of this transport regulation.
Transport hazard class(es):	No dangerous good in sense of this transport regulation.
Packing group:	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number:	No dangerous good in sense of this transport regulation.
Transport hazard class(es):	No dangerous good in sense of this transport regulation.
Packing group:	No dangerous good in sense of this transport regulation.

15. Regulatory information

U.S. Regulations

National regulatory information

SARA Section 304 CERCLA:
- Acrylic acid (79-10-7): Reportable quantity = 5,000 (2270) lbs. (kg)
- Maleic acid (110-16-7): Reportable quantity = 5,000 (2270) lbs. (kg)

SARA Section 311/312 Hazards:
- Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate (5888-33-5): Immediate (acute) health hazard
- 2-hydroxyethyl methacrylate (868-77-9): Immediate (acute) health hazard
- Acrylic acid (79-10-7): Fire hazard, Immediate (acute) health hazard
- Maleic acid (110-16-7): Immediate (acute) health hazard
- tert-butyl perbenzoate (614-45-9): Reactive, Immediate (acute) health hazard
- 3-methoxysilylpropyl methacrylate (2530-85-0): Immediate (acute) health hazard

SARA Section 313 Toxic release inventory:
- Acrylic acid (79-10-7): De minimis limit = 1.0 %, Reportable threshold = Standard

Clean Air Act Section 112(b):
- Acrylic acid (79-10-7)

State Regulations

Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

16. Other information

Changes

Revision date:	09/09/2026
Revision No:	2,15

This data sheet contains changes from the previous version in section(s): 2,11.

Other data

The above information describes exclusively the safety requirements of the product and is based on our

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)