Safety Data Sheet

Verifix 2K Silicone Primer

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Verifix 2K Silicone Primer

Further trade names

part of Set
BO 5500510, 1 kg
BO 5500513, 5 kg
BO 5500516, 50 kg
BO 5500518, 100 ml Primer

UFI: DT2F-PQ7M-39R3-7FEF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesion promotor

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name:	BOHLE AG	
Street:	Dieselstr. 10	
Place:	D-42781 Haan	
Telephone:	+49 2129 5568-0	Telefax: +49 2129 5568-282
E-mail:	info@bohle.de	
Contact person:	Dr. Martin Schade	Telephone: +49 2129 5568-300
E-mail:	MSDS@bohle.de	
Internet:	www.bohle.com	
Responsible Department:	Chemie	

Supplier

Company name:	Bohle Ltd
Street:	Fifth Avenue, Tameside Park
Place:	GB-SK14 6PP Dukinfield, Cheshire
Telephone:	0161 342 1100
E-mail:	info@bohle.ltd.uk

1.4. Emergency telephone number:

0344 892 0111
Office hours only.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT SE 3; H336
Asp. Tox. 1; H304
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements


Regulation (EC) No 1272/2008

Hazard components for labelling

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics
propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains trimethoxyvinylsilane; trimethoxy(vinyl)silane. May produce an allergic reaction.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves and eye protection/face protection.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P403+P235	Store in a well-ventilated place. Keep cool.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H304

Precautionary statements

P301+P312

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

HYDROGENATED POLY(C6-12 OLEFIN)

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics			> 90 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			10 - < 15 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-49-0	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics	> 90 %
	inhalation: LC50 = >20 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg		
67-63-0	200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	10 - < 15 %
	inhalation: LC50 = 30 mg/l (vapours); dermal: LD50 = 13400 mg/kg; oral: LD50 = 4570 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!
Move out of dangerous area.
Take off contaminated clothing and shoes immediately.

After inhalation

Remove casualty to fresh air and keep warm and at rest.
If symptoms persist, call a physician.

After contact with skin

Wash off with soap and plenty of water.
If symptoms persist, call a physician.

After contact with eyes

Rinse thoroughly with plenty of water, also under the eyelids. Remove contact lenses, if present and easy to do. Continue rinsing.
Consult a physician.

After ingestion

Rinse mouth thoroughly with water.
Do NOT induce vomiting.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2)
Extinguishing powder
alcohol resistant foam
Water spray jet

Unsuitable extinguishing media

high volume water jet

5.2. Special hazards arising from the substance or mixture

Heating or fire can release toxic gas.
Carbon dioxide, Carbon monoxide

5.3. Advice for firefighters

Standard procedure for chemical fires.
Self-contained respirator (breathing apparatus)

Additional information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protective equipment.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.
Do not allow to enter into soil/subsoil.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Other information

Provide adequate ventilation.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Dispose of waste according to applicable legislation.

6.4. Reference to other sections

Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations.
To avoid risks to man and the environment, comply with the instructions for use.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Usual measures for fire prevention.
Take precautionary measures against static discharges.
Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Do not breathe vapours or spray mist.
Avoid contact with skin, eyes and clothing. Take off all contaminated clothing immediately.
Wash hands before breaks and immediately after handling the product.
When using do not eat or drink. Do not smoke.
Keep away from food, drink and animal feedingstuffs.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.
Store in a place accessible by authorized persons only.
Protect from direct sunlight.

Hints on joint storage

Incompatible with oxidizing agents.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics			
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	2035 mg/m³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m³
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³
Worker DNEL, long-term		inhalation	systemic	500 mg/m³

PNEC values

CAS No	Substance	
Environmental compartment		Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater		140,9 mg/l
Freshwater (intermittent releases)		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Microorganisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Even in case of a full release, due to the small amount of substances present, it is not expected that exposure limits will be reached. However it is the duty of the user to verify this and follow given exposure limits at the workplace.

Individual protection measures, such as personal protective equipment

Eye/face protection

safety glasses with side-shields conforming to EN166

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.
Glove material: Butyl caoutchouc (butyl rubber), NBR (Nitrile rubber)
Take note of the information given by the producer concerning permeability and break through times , and of special workplace conditions (mechanical strain, duration of contact).

Skin protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.
EN 13034 (type 6 limited splash-tight)

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Combination filtering device
Respirator with filter for organic vapour, Recommended Filter type: A-P2

Environmental exposure controls

Do not flush into surface water or sanitary sewer system.
Do not allow to enter into soil/subsoil.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	clear	
Odour:	characteristic	
Boiling point or initial boiling point and boiling range:		60 °C
Lower explosion limits:		0,6
Upper explosion limits:		7,4
Flash point:		< 0 °C
Auto-ignition temperature:		>200 °C
pH-Value:		not applicable
Water solubility: (at 20 °C)		insoluble
Vapour pressure: (at 20 °C)		172 hPa
Density (at 20 °C):		0,7 g/cm³

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Other safety characteristics

Evaporation rate: (at 20 °C)	2,0
Solvent content:	94%
Solid content:	6%

Viscosity / dynamic: 0,55 mPa·s
(at 20 °C)

Further Information

Vapours can form explosive mixtures with air.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Protect from direct sunlight.

10.5. Incompatible materials

oxidizing agents

10.6. Hazardous decomposition products

No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg

Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics					
	oral	LD50 mg/kg	>5000	Rat		
	dermal	LD50 mg/kg	>2000	Rat		
	inhalation (4 h) vapour	LC50	>20 mg/l	Rat		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	oral	LD50 mg/kg	4570	Rat		
	dermal	LD50 mg/kg	13400	Rabbit		
	inhalation (4 h) vapour	LC50	30 mg/l	Rat		

Irritation and corrosivity

Causes skin irritation. May cause eye/skin irritation.
May cause eye irritation with susceptible persons.

11.2. Information on other hazards

Endocrine disrupting properties

This information is not available.

SECTION 12: Ecological information

12.1. Toxicity

This product has no known eco-toxicological effects.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] | [d]	Species	Source	Method
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics						
	Acute fish toxicity	LC50	11,4 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		OECD 203
	Acute algae toxicity	ErC50	30-100 mg/l	72 h	Pseudokirchneriella subcapitata		OECD 201
	Acute crustacea toxicity	EC50	3 mg/l	48 h	Daphnia		OECD 202
	Fish toxicity	NOEC	2,04 mg/l	28 d	Oncorhynchus mykiss (Rainbow trout)		
	Algae toxicity	NOEC	3 mg/l	3 d	Pseudokirchneriella subcapitata		OECD 201
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna (Big water flea)		OECD 211
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol						
	Acute fish toxicity	LC50	9640 mg/l	96 h	Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50	>2000 mg/l	72 h	Desmodesmus subspicatus		

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics			
	OECD 301F	98%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

Bioaccumulation is unlikely.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	-0,16

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.
The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not flush into surface water or sanitary sewer system.
Avoid subsoil penetration.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150107 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); glass packaging

Contaminated packaging

Dispose of completely emptied containers as combustible waste or metal waste depending on the material.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 3295
14.2. UN proper shipping name:	HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Classification code:	F1
Special Provisions:	640D
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 3295
14.2. UN proper shipping name:	HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Classification code:	F1
Special Provisions:	640D

Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 3295
14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: -
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3295
14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: A3 A324
Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
Entry 3, Entry 29, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 94 %

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,11.

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, hazard category 2
Asp. Tox. 1: Aspiration hazard, hazard category 1
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Irrit. 2: Eye irritation, hazard category 2
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2

Classification for mixtures and used evaluation method

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains trimethoxyvinylsilane; trimethoxy(vinyl)silane. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)